



## PERFORMANCE ENGINE OIL SERIES

**SAE 10W-30 API SM/CF**

**SOLMAX 1000**  
**Gasoline & Diesel Engines**

**SOLMAX 1000** Performance Engine Oil series is formulated for car and light commercial vehicles driven by gasoline, diesel or hybrid engines. The latest lubricant technology and premium additives are used in their formulations to ensure high performance and trustworthy protection. These lubricants are suitable for small to high output engines where modern city driving such as those associated with everyday stop-start traffic, can easily cause accelerated oxidation, sludge and varnish to the engine components. These lubricants give uncompromised protection to help power delivery and prolong engine life.

### RECOMMENDATION / BENEFITS

**SOLMAX 1000** oils contain high quality additive system to prevent premature shear-out associated with high performing modern engines. It is made with high shear-stable and engine-cleaning additives thus making it suitable for a wide range of gasoline and diesel engines. Operators of mixed fleet will be able to use these passenger cars motor oils (PCMO) for their whole range of vehicles for better inventory and cost control. Its robust formulation benefits...

- Superior protection to modern engines under demanding environments.
- Delivers smoother driving to performance gasoline, diesel, and gas engines.
- Protection against sludge and varnish build-up in the daily stop-start driving condition.
- Advanced protection for turbo-chargers, multivalve systems and catalytic converters.
- Formulated with premium quality Viscosity Index Improver (VII) delivering protection from high shearing modern engines thus ensuring high performance and long term protection.

### PERFORMANCE STANDARDS

- **SAE 10W-30** (SAE Viscosity Standards)
- **API SM/CF** (API Performance Category)

### PROPERTIES

DESCRIPTION	METHOD	TYPICAL VALUES
SAE VISCOSITY GRADE	SAE J 300	SAE 10W-30
Specific Gravity @ 15°C	ASTM D 4052	0.879
Pour Point, °C	ASTM D 97	-34
Flash Point, °C	ASTM D 92	231
Kinematic Viscosity @ 40°C	ASTM D 445	61.5
Kinematic Viscosity @ 100°C	ASTM D 445	10.5
Viscosity Index	ASTM D 2270	123
TBN (mg KOH/g)	ASTM D 2896	7.9
Colour	ASTM D 1500	<3.0

**AVAILABLE PACKAGING: 4L**

### SOLUTION BIOGEN SDN BHD

No. 3, Jalan TPK 2/4, Taman Perindustrian Kinrara, 47100 Puchong, Selangor, Malaysia

Tel: +60 3 8075 8000 Fax: +60 3 8075 5784 Email: sales@solmax.com.my Web: www.solmax.com.my

**All rights reserved.**

All materials data and specifications are based on as available and may change without prior notice.  
Please contact our sales & technical team for the latest information.